

Pt. 63, Subpt. JJJ, Table 2

40 CFR Ch. I (7–1–13 Edition)

Reference	Applies to Subpart JJJ	Explanation
§ 63.10(d)(3)	No	Subpart JJJ does not require opacity and visible emission standards.
§ 63.10(d)(4)	Yes.	Except that reports required by § 63.10(d)(5)(i) may be submitted at the same time as Periodic Reports specified in § 63.1335(e)(6). The start-up, shutdown, and malfunction plan, and any records or reports of start-up, shutdown, and malfunction do not apply to Group 2 emission points unless they are included in an emissions average.
§ 63.10(d)(5)(i)	Yes	
§ 63.10(d)(5)(ii)	No.	
§ 63.10(e)	No	§ 63.1335 specifies reporting requirements.
§ 63.10(f)	Yes.	§ 63.11(b) specifies requirements for flares used to comply with provisions of this subpart. § 63.1333(e) contains the requirements to conduct compliance demonstrations for flares subject to this subpart. § 63.11(c), (d), and (e) specifies requirements for an alternative work practice for equipment leaks.
§ 63.11	Yes	
§ 63.12	Yes	
§ 63.12	Yes	Except that the authority of § 63.1332(i) and the authority of § 63.177 (for equipment leaks) shall not be delegated to States.
§§ 63.13–63.15	Yes.	

^aThe plan and any records or reports of start-up, shutdown, and malfunction do not apply to Group 2 emission points unless they are included in an emissions average.

[66 FR 36939, July 16, 2001, as amended at 71 FR 20460, Apr. 20, 2006; 73 FR 78214, Dec. 22, 2008]

TABLE 2 TO SUBPART JJJ OF PART 63—GROUP 1 STORAGE VESSELS AT EXISTING AFFECTED SOURCES

Vessel capacity (cubic meters)	Vapor pressure ^a (kilopascals)
75≤capacity 151	≥13.1
151≤capacity	≥5.2

^aMaximum true vapor pressure of total organic HAP at storage temperature.

[65 FR 38142, June 19, 2000]

TABLE 3 TO SUBPART JJJ OF PART 63—GROUP 1 STORAGE VESSELS AT EXISTING AFFECTED SOURCES PRODUCING THE LISTED THERMOPLASTICS

Thermoplastic	Chemical ^a	Vessel capacity (cubic meters)	Vapor pressure ^b (kilopascals)
ASA/AMSAN ^c	styrene/acrylonitrile mixture	≥ 3.78	≥ 0.47
	acrylonitrile	≥ 75.7	≥ 1.62
Polystyrene, continuous processes	all chemicals	<75.7	≥ 14.2
		≥ 75.7.	
Nitrile ^c	acrylonitrile	≥ 13.25	≥ 1.9
			≥ 1.8

^aVessel capacity and vapor pressure criteria are specific to the listed chemical or to "all chemicals," as indicated.

^bMaximum true vapor pressure of total organic HAP at storage temperature.

^cThe applicability criteria in Table 2 of this subpart shall be used for chemicals not specifically listed in this table (i.e., Table 3).

[64 FR 11553, Mar. 9, 1999]

TABLE 4 TO SUBPART JJJ OF PART 63—GROUP 1 STORAGE VESSELS AT NEW AFFECTED SOURCES

Vessel capacity (cubic meters)	Vapor pressure ^a (kilopascals)
38 ≤ capacity < 151	≥13.1
151 ≤ capacity	≥0.7

^aMaximum true vapor pressure of total organic HAP at storage temperature.